

US005784377A

# United States Patent [19]

Baydar et al.

[11] Patent Number:

5,784,377

[45] Date of Patent:

Jul. 21, 1998

#### [54] INTEGRATED DIGITAL LOOP CARRIER SYSTEM WITH VIRTUAL TRIBUTARY MAPPER CIRCUIT

[75] Inventors: Ertugrul Baydar, Grapevine, Tex.; J.
Bradley Boudreaux, Stephens City,
Va.; Nicholas Carter, Chantilly, Va.;
Chung Chen, Herndon, Va.; Steven
Klonsky, Arlington, Va.; Michael
Moran, Darien, Ill.; Peter Renucci,
Grapevine, Tex.; Jeffrey Timbs, Keller,
Tex.; Thomas Tucker, Washington,
D.C.; Waleed Wardak, Grapevine, Tex.

[73] Assignee: Hubbell Incorporated, Orange, Conn.

[21] Appl. No.: 471,224

[22] Filed: Jun. 6, 1995

#### Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 31,395, Mar. 9, 1993, abandoned, and a continuation-in-part of Ser. No. 251,848, May 31, 1994, abandoned.

13

370/386

# [56] References Cited

### U.S. PATENT DOCUMENTS

| 4,811,340 | 3/1989  | McEachern et al | 370/102 |
|-----------|---------|-----------------|---------|
| 4,888,765 | 12/1989 | Dyke            | 370/95  |

(List continued on next page.)

#### OTHER PUBLICATIONS

Table of Contents for Bellcore Technical Reference TR-NWT-000253 on Synchronous Optical Network (SONET) Transport Systems: Common Generic Criteria. Dec. 1991.

Table of Contents for Bellcore Technical Reference TR-NWT-00496 on SONET Add-Drop Multiplex Equipment (SONET ADM) Generic Criteria, May 1992.

Table of Contents for Bellcore Technical Reference TR-TSY-000008 on Digital Interface Between the SLC 96 Digital Loop Carrier System and A Local Digital Switch, Aug. 1987.

Table of Contents for Bellcore Technical Reference TR-TSY-00303 on IDLC System Requirements. Objectives, and Interface. Oct. 1989.

#### (List continued on next page.)

Primary Examiner—Wellington Chin Assistant Examiner—Huy D. Vu Attorney, Agent, or Firm—Roylance, Abrams, Berdo & Goodman, L.L.P.

### [57] ABSTRACT

An integrated digital loop carrier (IDLC) system includes digital line feeders and signal processors to interface with the feeders and to ultimately provide data to subscriber instruments. The system can be employed as a central office terminal (COT) or remote digital terminal (RDT) with analog, T1 or SONET feeders and any conventional link medium. Data are put in DS1 format and multiplexed onto optical loops for delivery to banks of channel units wherein the optical signals are translated to electrical signals for delivery to the channel units and subscribers. A method and apparatus is provided for mapping and demapping signals between virtual tributaries (VT) and digital signal formats in the RDT of an integrated digital loop carrier. An applicationspecific circuit provides such mapping and demapping functions as Floating Byte Synchronous VT to Locked Byte Synchronous VT. Floating Asynchronous VT to Locked Byte Synchronous VT, Floating Asynchronous VT to Floating Asynchronous VT. DS1 to Locked Byte Synchronous VT. DS1 to Floating Asynchronous VT, and DS1 to Floating Byte Synchronous VT.

## 30 Claims, 72 Drawing Sheets

